

CONTAINER



Total protection

Thanks to resistance to salty atmosphere, UV rays and overtemperatures.



AC3-AC23A

Thanks to the isolator switch at rated current.



Per container

Thanks to 380/440V, 3h, 32A plugs and sockets, the power supply of refrigerated containers is guaranteed.



Compliance with standards	IEC/EN 60309-1 IEC/EN 60309-2 CEI EN 60309-4
Protection rating (IP according to IEC/EN 60529)	Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46
Rated current	32A 3P+\neq 3h
Operating voltage	380/440V
Operating frequency	50-60Hz
Storage temperature	Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46
Operating temperature	Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46



Rated operating currentswitch:			32A
Thermal current Ith		A	32
AC21A	400V	A	32
AC22A	400V	A	32
AC23A	400V	A	32
AC23A	400V	kW	15
AC3	400V	kW	15

THERMOSETTING GRP

M32 ENTRY



Interlocked socket-outlet
in thermosetting GRP
with **MCB** for wall-mounting
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ \neq	3	474771	1


M25 ENTRY



Interlocked socket-outlet
in thermosetting GRP
for wall-mounting
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ \neq	3	469233	1


M32 ENTRY



Interlocked socket-outlet
in thermosetting GRP
for wall-mounting
and **DIN rail**
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ \neq	3	472133	1

Technical accessories:




page 163



ALUMINIUM

WINDOW F1



Interlocked socket-outlet
in aluminium alloy
with **MCB**
for wall-mounting
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	474486	1


WINDOW F1



Interlocked socket-outlet
in aluminium alloy
for wall-mounting
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	460233	1

WINDOW F1



Interlocked socket-outlet
in aluminium alloy
with **DIN rail**
for wall-mounting
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	472735	1

Technical accessories:



page 158

THERMOPLASTIC



Interlocked socket-outlet
for distribution boards
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	491233	1

Technical accessories:



page 74



15° angled
flush-mounted fixed socket
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	88x100	3P+≐	3	489233	1

Technical accessories:



page 35

page 35



TECHNOPOLYMER



Straight panel-mounted socket
50-60Hz
IP66/IP67/IP68/IP69

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	65x83	3P+≐	3	772233	1

Technical accessories:



page 91



Coupler
50-60Hz
IP66/IP67/IP68/IP69

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	88x100	3P+≐	3	770233	1



Straight panel-mounted rotoswitched socket
50-60Hz
IP66/IP67/IP69

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	65x83	3P+≐	3	412233	1

Technical accessories:



page 91


page 91



Plug
50-60Hz
IP66/IP67/IP68/IP69

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	760233	1

Technical accessories:



page 47