
RINO-EX Series

Zones 2, 21, 22

LIGHTING FIXTURES IN STAILESS STEEL



Watertight light fixtures in aluminium alloy suitable for applications in explosion hazardous areas as defined in ATEX Directive 2014/34/EU.

Χ

USABLE

The body of the light fixture is treated with ecological anti-corrosion passivation with fluoro-zirconium and finished with hot polymerised scratch-resistant painting. non-toxic non-ageing polyester The colour of the body is light grey RAL 7035. The diffuser is in prismatic tempered glass. The steel wire protection cage is RAL 2011 deep orange and is attached to the body by means of stainless steel screws while the sealing is guaranteed by a reinforced gasket in non-ageing elastomer. Predisposed for entry through an M20 cable gland. Complete with internal and external earth screw.

Compliance with standards	Directive ATEX 2014/34/EU EN 60079-0 EN 60079-15 EN 60079-31 Directive 2014/35/EU EN 60598-1 EN 60598-2-1 Directive 2011/65/EU EN 50581
ATEX execution	 II 3G 2D Ex nA IIC T3 Gc Ex tb IIIC T 75/85/90 °C Db
Casing material	Aluminium alloy
Surface treatment	Passivation with fluoro-zirconium treatment
Paint	Hot polymerised non-toxic, non-ageing polyester
Colour	RAL 7035 (light grey) Back box
	RAL 2011 (deep orange) Protection cage
Diffuser material	Prismatic tempered glass
Protection rating (IP according to IEC/EN 60529)	IP65
Protective cage material	Painted tropicalized steel wire
Supply voltage	230V
Operating frequency	50-60Hz
Max conductor cross-section	2,5 mm²
Entry cable diameter	10 - 14 mm
Lamp holder type	E27 in porcelain
Insulation class	ı
Operating temperature	-20°C ÷ +40°C



Technical data sheets updated to new standards on palazzoli.com website



SUITABLE FOR ZONES 2 (GAS) AND 21-22 (DUST)



Oval light fixtures in aluminium alloy with steel protective cage IP65

Power (W)	Dimensions (mm)	Palazzoli code	Pack Qty
18	199x112	831072EX	1
28	226x130	831172EX	1
53	295x170	831272EX	1

Equipment included: internal and external earth screw and cable gland.




Round light fixtures in aluminium alloy with steel protective cage IP65

Power	Dimensions	Palazzoli	Pack
(W)	(mm)	code	Qty
28	200x182	830072EX	1

Equipment included: internal and external earth screw and cable gland.

Light fixture/lamp selection



Dimensions

Type bulb	Power halogen lamps* (W)	A (mm)	B (mm)
1894	18	90	38
	28	110	40
	53	168	43
	28	90	38

*The certification is valid only with the use of halogen lamps.