

The SkySwitch Nema StreetLight Photocell has a 5 year warranty. Especially designed to guarantee maximum operating life through use of the highest grade components including ultra long-life capacitors and through-hole plating.




Specification

Fixing (where applicable hole dimensions)	Nema 3-pin (also suitable for 5/ 7-pin)
70 Lux Switch-On Level	Yes
55 Lux (on 55 / off 28)	Option
35 Lux (on 35 / off 18)	Option
20 Lux (on 20/ off 20)	Option
Switching ratio	1:1 or 1:0.5
Capable of unity or negative ratio	Yes
Maximum total load for discharge lighting (eg: HPS, MH) (Watts)	800
Maximum total load for incandescent lighting (watts)	800
Maximum total load for LED lighting (watts)	800
Polycarbonate Enclosure (UV) stabilised	Yes
Consumption in watts	<0.25
Sensor Type	Filtered Photodiode
Sensor Drift	Negligible
Max operating ambient temp range	-20/+80
IP Rating (installed)	IP67
Voltage	198 - 270V
Frequency	47-63Hz
Electro-magnetic Relay	Yes

Dimensions

Height	50mm (71mm inc fitting)
Width	80mm



Benefits

- Long Life: Superior quality components
- Energy Saving: <0.25W power consumption
- Excellent light sensor: High grade filtered photodiode
- Solid State Relay: Zero cross switching
- Proven Reliability: 15 years design life