




**SERIES ALARM-Ex
SIREN**
CODE 900453EX



Datasheet

Specifications

Net Weight	1,256 G
Rated current	2.5A
Frequency	50/60Hz
Protection degree	IP66
Poles	2P+ \perp
Rated operating voltage	24V
Manufacturing material	Aluminium alloy (EN 46100)
Hole type	M20
Sound level at 1 mt.	107/105dB
Acoustic Signal Type	D - continuous sound according to manual control
Operational working temp	-20 T 40

Warranties, Reference Standards and Directives

Warranty	1 years
Certification and approval marks	IECEX, TUV EX, NYCE COLOMBIA, CE, EX
Directives	2014/34/EU (ATEX), 2014/30/EU (EMC), 2012/19/EU (WEEE), 2011/65/EU (RoHS), 2014/35/EU (LVD)
Reference Standards	EN 62080:2009 , EN 63000:2018, EN 60079 0/A11:2013, EN 50581:2012, EN 60079 31:2014, EN 60079-0:2012, EN 60079 15:2010

Atex characteristics

ATEX application zone	Zona/Zone 2, 21 and 22
Dust Atex execution	II 2D - Ex tb IIIC T65 °C Db
Gas Atex execution	II 3G - Ex nA IIC T3 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.