

# Product data sheet

Specifications



## SpaceLogic KNX USB Interface DIN Rail

MTN6502-0101

### Main

Range	SpaceLogic KNX
Product or component type	USB interface
Bus type	KNX
Colour tint	Schneider white
Colour code	RAL 9003
Market segment	Residential Commercial

### Complementary

Connector type	USB type C
Communication port protocol	USB KNX KNX long frame
Transmission rate	12 Mbit/s 9600 bit/s
Total number of 18 mm modules	1
Local signalling	2 LEDs
Material	PC
Mounting support	DIN rail
Function available	Supports KNX Secure

### Environment

Relative humidity	5...93 %
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-5...45 °C
Standards	EMC directive EN 50491-3 EN 50491-5-2 EN 50491-5-3 EN 61000-6-2 EN 61000-6-3 EN 50581 : 2012
IP degree of protection	IP20

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	82.0 g
Package 1 Height	6.0 cm
Package 1 width	7.0 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Weight	5.717 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins