

Product data sheet

Specifications



SpaceLogic KNX DALI Gateway Pro 1ch DALI-2

MTN6725-0101

Main

Range of product	SpaceLogic KNX
Product or component type	KNX DALI gateway
Bus type	KNX
Function available	Updateable software

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
Communication port protocol	DALI
Web services	HTTP server
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	275.0 g
Package 1 Height	8.0 cm
Package 1 width	12.5 cm
Package 1 Length	15.7 cm
Unit Type of Package 2	P12
Number of Units in Package 2	112
Package 2 Weight	47.0 kg
Package 2 Height	45.0 cm
Package 2 width	80.0 cm
Package 2 Length	120.0 cm

Unit Type of Package 3	S04
Number of Units in Package 3	28
Package 3 Weight	8.603 kg
Package 3 Height	30.0 cm
Package 3 width	40.0 cm
Package 3 Length	60.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins